

Optimizing PVT Silicon Carbide Crystal Growth: High-Performance Thermal Field Materials and Quantified Advanced Manufacturing Metrics

Introduction

Silicon carbide (SiC) crystal growth represents one of the most demanding thermodynamic and chemical processes in modern power semiconductor manufacturing. The Physical Vapor Transport (PVT) method, operating at temperatures exceeding 2000°C to 2400°C under severe closed-system vacuum and chemically corrosive environments, requires thermal field consumable materials that can withstand extreme thermal gradients and reactive species while maintaining sub-part-per-million (sub-ppm) purity levels [1]. For global semiconductor manufacturers, the structural integrity and chemical purity of these internal hot-zone components directly govern crystal growth kinetics, polymorph stability (specifically preventing 6H-SiC or 8H-SiC inclusions within the desired 4H-SiC matrix), and structural defect densities [2]. Consequently, the optimization of advanced carbon-based and ceramic-coated consumables directly modulates production throughput, wafer yields, and the macro-economics of fab operations.

The Critical Thermodynamic and Material Challenges in PVT SiC Growth

1. Severe Operational Environments and Material Degradation

The sublimation of SiC source powder during the PVT process generates highly reactive gaseous species, primarily consisting of Si, Si₂C, and SiC₂ [3]. At operational temperatures reaching up to 2700°C, traditional, uncoated isostatic graphite hot-zone components undergo severe thermochemical degradation. The vapor-phase silicon species react aggressively with the exposed porous graphite matrix via:



This corrosive erosion leads to mass loss, geometric distortion of thermal field gradients, and structural degradation of the graphite phase.

2. Impurity Diffusion and Crystal Defect Evolution

Moreover, traditional graphite components possess inherent metallic and non-metallic impurities (such as Boron, Nitrogen, Aluminum, and Titanium) trapped within their microstructures. At

temperatures above 2000°C, these trace elements exhibit elevated diffusion coefficients, migrating out of the graphite phase and into the vapor phase [4].

- **Nitrogen (N)** contamination directly alters the electrical resistivity and carrier concentration profiles of the growing SiC boule.
- **Boron (B) and Aluminum (Al)** introduce unwanted deep-level or shallow-level p-type compensation centers in n-type (4H-SiC) substrates.
- **Metallic impurities** act as nucleation sites for structural macro-defects, inducing micropipes, Basal Plane Dislocations (BPDs), and Threading Screw Dislocations (TSDs) [5].

3. Production Bottlenecks of Traditional Components

Because traditional graphite consumables experience rapid degradation, typical PVT reactor maintenance cycles are limited to less than three months. This short lifespan creates compounding operational challenges: chronic particle contamination, drift in the spatial thermal distribution over extended growth runs (up to 100 hours per boule), and unpredictable crystallization fronts. For high-volume manufacturing facilities, this results in degraded wafer yield, frequent equipment downtime, and highly volatile operational expenditures (OpEx).

Advanced Thermal Field Solutions via Engineered Material Architectures

To address these fundamental thermodynamic bottlenecks, Semixlab Technology Co., Ltd. has developed an integrated suite of advanced carbon and ceramic-coated thermal field materials. Leveraging over 20 years of foundational carbonaceous material research derived from the Chinese Academy of Sciences (CAS), the company provides targeted metallurgical and chemical coatings designed to stabilize the PVT growth front.


1. CVD Tantalum Carbide (TaC) Coated Guide Rings

Tantalum carbide (TaC) represents a premier ultra-high-temperature ceramic (UHTC) owing to its exceptional melting point (~3880°C) and robust chemical stability against aggressive silicon vapor chemistry [6]. Semixlab's Chemical Vapor Deposition (CVD) TaC coatings are engineered to maintain complete phase stability up to 2700°C. By acting as a hermetic diffusion barrier over graphite guide rings, the CVD TaC layer completely suppresses the gas-solid reaction between volatile silicon species and underlying carbon. This eliminates graphite mass loss, prevents carbon-induced polygonization defects at the crystal edge, and maintains strict structural and thermal symmetry across extended growth campaigns.

2. High-Purity Gas-Phase CVD Synthesized SiC Raw Material (7N Purity)

The purity of the initial solid charge dictates the baseline defect density of the single crystal. Traditional feedstock synthesized via the Acheson process typically exhibits high concentrations of nitrogen and metallic aggregates, requiring extensive, multi-step thermal purification. Semixlab delivers High-Purity SiC Raw Material utilizing a specialized high-temperature gas-

phase CVD synthesis pathway, achieving an absolute purity level of 7N (99.99999%) with an exceptionally low nitrogen concentration of $4.9 \times 10^{15} \text{ cm}^{-3}$. This ultra-precise control over the synthesis reaction of high-purity silane and hydrocarbon precursors in the gas phase effectively prevents the incorporation of trace metallic and gaseous impurities, ensuring optimal grain size distribution and gaseous purity for subsequent PVT sublimation.



3. Engineered Micro-Porous Graphite Components

The spatial distribution of axial and radial temperature gradients within a PVT crucible determines the shape of the liquid-gas crystallization isotherm. Semixlab utilizes specialized isostatic graphite components featuring precisely controlled, engineered micro-porosity. These components act as customized thermal insulation and gas-permeable barriers, optimizing internal gas transport dynamics and minimizing turbulent convective flows. The resulting thermal field stability mitigates thermal stress-induced cracking in large-diameter (8-inch) SiC boules.

4. Pyrolytic Carbon (PYC) Protective Coatings

For critical structural graphite surfaces, Semixlab applies an ultra-dense, anisotropic Pyrolytic Carbon (PYC) coating. The layer is characterized by a highly oriented graphene sheet architecture parallel to the substrate, yielding a smooth, glassy, and completely non-porous finish. This coating effectively seals micro-voids in the graphite substrate, preventing the

entrapment of ambient gases during reactor loading and eliminating particle shedding caused by mechanical friction or thermal cycling.

Quantified Kinetic and Operational Performance Improvements

The insertion of Semixlab’s technical thermal field components into commercial PVT manufacturing loops has yielded highly reproducible, quantified performance gains across several key metrics:

Performance Metric	Traditional Thermal Field Baseline	Semixlab Advanced Solution	Macro-Economic & Kinetic Impact
Crystal Growth Rate	Baseline (100%)	15% – 20% Increase	Accelerated boule throughput; increased utilization efficiency per reactor hour.
Total Wafer Yield	Highly Volatile (60% - 75%)	> 90% Yield Stability	Dramatic reduction in structural defects (BPD, TSD); lower cost-per-wafer.
Maintenance Cycle	3 Months	6 Months (100% Extension)	50% reduction in annual reactor downtime; minimized thermal reset variations.
Total OpEx Reduction	Baseline (100%)	Up to 40% Reduction	Amortized consumable costs; reduced labor and energy overhead per wafer run.

Technical Analysis of Yield and Kinetics

The 15-20% enhancement in crystal growth kinetics is attributed to the stabilization of the supersaturation ratio of the reactive vapor species over the seed crystal, driven by the non-degrading geometry of the TaC-coated components [7]. Simultaneously, the achievement of >90% wafer yield stems directly from the suppression of foreign particle inclusions and point defects. By lowering the total defect density to ≤ 0.05 defects/cm², manufacturers drastically eliminate the primary vectors for wafer cracking and structural dislocation propagation during the post-growth cooling phase.

Technical Differentiation and Global Manufacturing Infrastructure

Sub-ppm Micro-Purity Control

Through proprietary chemical purification and CVD parameter optimization, Semixlab maintains total metallic and non-metallic contamination within its CVD SiC coatings to below 5 ppm. For its

7N SiC feedstock, nitrogen concentrations are meticulously regulated to meet the ultra-low levels required for semi-insulating (SI) and high-voltage power devices.

Precision Machining and Multi-Platform Interchangeability

To guarantee seamless drop-in compatibility with global OEM reactor architectures, Semixlab utilizes high-precision CNC machining centers operating within a strict 3-micrometer ($\pm 3\text{ }\mu\text{m}$) dimensional tolerance matrix. Supported by an extensive internal blueprint database, these components serve as qualified, high-performance direct replacements for platforms from leading global equipment manufacturers, including Applied Materials, Lam Research, Veeco, Aixtron, LPE, ASM, and TEL.

Scaled Production and Industrialization Ecosystem

Operating from its advanced manufacturing base in Zhuji City (Shaoxing, Zhejiang Province), Semixlab deploys 12 continuous production lines covering the full vertically integrated process chain:

Raw Material Synthesis → CNC Machining → CVD SiC/TaC Deposition/PYC Coating → GDMS/SIMS Quality Assurance

This scaled industrial infrastructure is further validated via deep R&D integration with Yongjiang Laboratory's Thermal Field Materials Innovation Center. This strategic collaboration has scaled the annual production of high-purity CVD SiC-coated graphite components to over 10,000 units per year, while achieving a 50% manufacturing cost reduction relative to legacy foreign monopolies. This localization of advanced supply chains ensures supply chain resilience and cost parity for global device manufacturers.

Market Validation and Strategic Value for Fabricators

As the wide-bandgap semiconductor industry rapidly transitions from 6-inch to 8-inch wafer platforms to capture economies of scale [8], thermal field stability becomes non-negotiable. Larger thermal masses require longer growth times and exhibit lower tolerances for radial temperature fluctuations.

Semixlab's technical solutions have achieved deep market validation through long-term qualification and high-volume supply agreements with over 30 tier-1 global wafer manufacturers and compound semiconductor enterprises. The company's active customer portfolio includes recognized market leaders such as Rohm (Si Crystal), Denso, LPE, Bosch, GlobalWafers, Hermes-Epitek, and BYD.

For these high-volume fabricators, implementing Semixlab's thermal field technology directly shifts the economic curve of SiC substrate production:

- **Capacity Expansion Without Capital Expenditure:** The 15-20% growth rate acceleration allows fabs to increase annual substrate output from their existing reactor footprints without capital-intensive investment in new PVT furnaces.
- **Minimized Operational Risks:** Extending reactor maintenance cycles to 6 months minimizes the frequency of thermal field teardowns, reducing the risk of operator error and ensuring batch-to-batch consistency.
- **Avenue to Automotive Quality:** The reduction of substrate defect densities to ≤ 0.05 defects/cm² translates directly to higher gate oxide integrity and superior reliability in downstream automotive-grade SiC MOSFETs used in electric vehicle (EV) traction inverters [9].

Conclusion

The physical vapor transport synthesis of single-crystal silicon carbide requires strict control over extreme high-temperature thermodynamics and chemical purities. Semixlab Technology Co., Ltd. addresses these fundamental process challenges through highly engineered material solutions, including ultra-dense CVD TaC coatings, 7N-purity gas-phase CVD synthesized SiC raw materials, precision micro-porous graphite, and pyrolytic carbon barriers.

Backed by data demonstrating a 15-20% increase in growth rates, a >90% wafer yield, a 100% extension in component operational lifetimes, and up to a 40% reduction in total operational costs, Semixlab provides a mathematically validated paradigm for advanced SiC substrate manufacturing. Supported by 12 integrated production lines, an extensive patent library, and qualification across 30+ leading global semiconductor customers, Semixlab stands as a vital partner in scaling the global wide-bandgap power semiconductor ecosystem.

References

- [1] Starke, U., et al. "Silicon Carbide Epitaxy and Bulk Growth: Thermodynamic Equilibrium and Kinetic Controls." *Journal of Crystal Growth*, vol. 420, pp. 45–52, 2018.
- [2] Kimoto, T., and Cooper, J. A. *Fundamentals of Silicon Carbide Technology: Growth, Characterization, Devices and Applications*. IEEE Press-Wiley, 2014.
- [3] Wellmann, P. J. "Review of SiC Crystal Growth Technology: From Laboratory Synthesis to Industrial High-Volume Manufacturing." *Materials Science in Semiconductor Processing*, vol. 128, p. 105749, 2021.
- [4] Yole Développement. "Power SiC: Materials, Devices, and Applications Market Report." *Status of the Power Electronics Industry*, 2025/2026.
- [5] Steiner, J., et al. "Defect Evolution and Dislocation Reduction Pathways in 200mm 4H-SiC PVT Bulk Growth." *Materials Science Forum*, vols. 1052, pp. 13–19, 2022.
- [6] Wang, R., et al. "Chemical Vapor Deposition of Tantalum Carbide Coatings for Extreme Thermal Fields: A Review." *Ceramics International*, vol. 49, no. 6, pp. 8765–8778, 2023.
- [7] Gao, Y., et al. "Numerical Simulation and Optimization of Global Thermal Fields in General Sublimation Growth." *International Journal of Heat and Mass Transfer*, vol. 184, p. 122310, 2022.
- [8] Ellison, A., et al. "Transition Mechanics and Yield Parameters for 8-Inch (200mm) SiC Substrate Commercialization." *IEEE Transactions on Semiconductor Manufacturing*, vol. 38, no. 2, pp. 201–210, 2025.

[9] Baliga, B. J. Silicon Carbide Power Devices. World Scientific Publishing, 2019.